
number of links are removed.

Reassembly: Rejoin bracelet parts. Push pin back into link in opposite direction of arrow. Press pin down securely into bracelet until it is flush.

SOLID LINK BRACELET

Removing Links: Using a very small screw-driver, remove screws by turning counter-clockwise. Repeat until desired number of links are removed. Do not remove links adjacent to clasp.



Reassembly: Rejoin bracelet parts and insert screw in end of opening where it was removed. Turn screw clockwise until tight and flush with bracelet.

WATER AND SHOCK RESISTANCE

WARNING: TO MAINTAIN WATER-RESISTANCE, DO NOT PRESS ANY BUTTONS OR PULL OUT THE CROWN UNDER WATER UNLESS YOUR WATCH IS INDICATED AS 200 METER WATER-RESISTANT.

1. Watch is water-resistant only as long as crystal, crown and case remain intact.
2. Watch is not a diver watch and should not be used for diving.
3. Screw-in setting crown and case back must be screwed into case to assure water-resistance (see Set Time). (Optional)
4. Rinse watch with fresh water after exposure to salt water.
5. Shock-resistance will be indicated on watch face or caseback. Watches are designed to pass ISO test for shock-resistance. However avoid damaging crystal/lens.

If your watch is water-resistant, meter marking or (≈) is indicated.

Water-Resistance Depth	p.s.i.a.* Water Pressure Below Surface
30m/98ft	**60**
50m/164ft	**86**
100m/328ft	**160**
200m/656ft	**284**

*pounds per square inch absolute

BATTERY

Timex strongly recommends that a retailer or jeweler replace battery. If applicable, push reset button when replacing battery. Battery type is indicated on caseback. Battery life estimates are based on certain assumptions regarding usage; battery life may vary depending on actual usage.

DO NOT DISPOSE OF BATTERY IN FIRE. DO NOT RECHARGE. KEEP LOOSE BATTERIES AWAY FROM CHILDREN.

tous les maillons désirés.

Réassemblage : Réassem
clavette dans le maillon en
Enfoncer la clavette jusqu'
bracelet.

BRACELET À MAILLONS V

Retrait des maillons : À l'
tournevis, retirer les vis en
SENS ANTIHORAIRE. Répe
jusqu'à l'obtention du nom
Ne pas retirer les maillons

Réassemblage : Réassem
bracelet et insérer la vis à
maillons. Tourner la vis dan
serrée à fleur du bracelet.

ÉTANCHÉITÉ

**MISE EN GARDE : POUR A
SUR LES POUSSOIRS NI T
TRE EST IMMERGÉE, À M
D'ÉTANCHÉITÉ À 200 MÈ**

1. La montre est étanche u
couronne et le boîtier re
2. La montre n'est pas con
pour la plongée.
3. La couronne vissable de
vissés dans le boîtier po
l'heure). (En option)
4. Rincer la montre à l'eau
5. La résistance aux chocs
l'endos du boîtier. Les m
l'ISO pour la résistance
cristal ou la lentille.

Si la montre est étanche, la

Profondeur d'étanchéité
30m/98ft
50m/164ft
100m/328ft
200m/656ft

*livres par pouce carré absolu

**Timex recommande fort
place la pile.** Si applicable,
de remplacer la pile. Le typ
L'estimation de la durée de
quant à l'usage; sa durée r

NE PAS JETER LA PILE AU